

# Model 303-100

## High Power Pulsed Nd: YAG Laser



The 303 Series Pulsed Nd: YAG Laser is designed with a small beam diameter and low beam divergence to deliver exceptionally high brightness for precision drilling, cutting, and welding applications.

<b>Performance</b>	
Wavelength	1064 nm
Maximum Average Power	100 watts
Maximum Energy Per Pulse	30 J
Repetition Rate	0 - 200 Hz
Pulse Width	0.2 - 20 ms
Beam Diameter	6.3 mm
Beam Divergence	2 - 6 (mr-full angle)
Mode Structure	multimode
<b>Input Power Requirements</b>	
Voltage (standard)	208/230 V, 3 $\Phi$ , 50 – 60 Hz
Power Consumption (max)	7 KW (Peak)
<b>Cooling Water Requirements</b>	
Temperature	< 55° F.
Flow	3 gal/min
Pressure	40 – 60 psi
<b>Dimensions</b>	
Optical Assembly	46" (L) x 10" (W) x 9" (H)
Power Supply	22" (W) x 33" (D) x 39" (H)

- Touch Screen Controller provides ease of programming.
- Available with Conventional, Fiber Optic, or Galvanometer Beam Delivery.
- Beam Multiplexer available for time or beam sharing output.
- Simmer Mode Power Supply provides extended lamp life and improved pulse-to-pulse stability.
- High Efficiency Cooler with Proportioning Valve Control maintains even rod and lamp temperatures for better stability.

**U.S. LASER**  
CORPORATION



825 Windham Court North, Wyckoff, NJ 07481  
Tel: 201-848-9200 Fax: 201-848-9006  
[www.uslasercorp.com](http://www.uslasercorp.com)