

Model 486/486Q

High Power, Diode-Pumped CW & Q-Switched Nd: YAG Laser



The innovative laser optics design and industrial-grade power supply of the Model 486/486Q provides an extraordinarily reliable and rugged choice for industrial use. A totally solid state laser for trouble-free manufacturing!

Performance		
Wavelength	1.064 μ m	
Transverse Mode	Multimode	
Beam Diameter	5 mm	
Beam Divergence	<12 mr	
Polarization	Random	
CW (Continuous) Performance		
Output Power	150 Watts	
Stability	2 % rms	
Q-Switched (Pulsed) Performance		
Frequency	1 kHz	10 kHz
Average Power	20 Watts	75 Watts
Pulse Width	<80 ns	<120 ns
Peak Pulse Power	250 kW	63 kW
Pulse Stability	4 % rms	5 % rms
Mechanical		
Optical Rail Length	46" (L) x 9 1/2" (W) x 9" (H)	
Power Supply Dimension	39" (H) x 22" (W) x 33" (D)	
Electrical Power		
Recommended Service	220 \pm 10% VAC, 1 Φ , 50/60 Hz, 30A	
Average Consumption	6.0 kW, Maximum	
Cooling		
Internal, Water/Water Cooler	No external water required	

- Efficient diode optical pumping for improved performance and reliability.
- High power from small diameter, low divergence beam.
- Highly circular multimode beam profile.

U.S. LASER
CORPORATION



825 Windham Court North, Wyckoff, NJ 07481
Tel: 201-848-9200 Fax: 201-848-9006
www.uslasercorp.com